



StickApp & StickApp Plus



Add value to your reject boards!



















Add value to your reject boards with the regularising saw Brødbæk StickApp & StickApp Plus

The standard line **Brødbæk StickApp** features:

- Magazine for a stack of random width boards
- Infeed chain with steel dogs for positive feeding
- Vertical saw for setting up blades for cutting boards or sticks depending on spacers between the blades
- 2 outfeed rollers driven by gear motor
- Pneumatic operated idle top pressure roll
- Belt conveyor for finished boards and sticks, means higher capacity.

OPTION

The extended version **Brødbæk StickApp Plus** also includes:

- Horizontal saw with saw bush for setting up 1 blade for calibration of board thickness
- Thickness can be adjusted by changing spacer.

Basic data for the BCO Stick App

Board length mm 800 – 1,250 (1,900)

Board width mm 75 - 150Board thickness mm 15 - 30

Feeding speed, max. m/min. 40. Depending on cutting pattern

Max. capacity boards/min. 22 pcs. at length 1,250 mm

Diameter, vertical saw blade mm 360

Kerf mm 3.9. Depending on saw blade manufacturer specs.

Machine frame, length x width mm $4,300 \times 2,500$

Power, 3 x 400 V, 50 Hz kW 78

Extraction points mm $2 \times \emptyset$ 140 Air flow m³/hour 3,450

Weight with motors kg 3,500

Additional data for the BCO Stick App+

Diameter, horizontal saw blade mm 540
Kerf mm 10
Equalizing depth mm 0-10

Common features:

- One steel frame for easy flexible installation
- Variable feed speed, frequency controlled
- Mechanical & electric safety features
- "Wired, tested & ready to go!"



Infeed magazine for a stack of random width boards. At the bottom is the infeed chain with steel dogs, for a positive feeding of even wet boards.



To the left is the **StickApp Plus** unit with a horizontal saw bush for calibrating the thickness of boards and sticks.



The basic **Stick App** unit with a vertical saw for cutting boards and sticks.



The control cabinet. Insert: The HMI-unit.

Brødbæk & Co. A/S Mølgårdvej 1 DK-7173 Vonge Denmark

管: +45 7580 3599 Fax: +45 7580 3581 E-mail: sales@brodbaek.dk Website: www.brodbaek.dk

_						_		
D	\sim	ar.	\sim	on	ıta	ŧ۱۰	10	